

Mobile and IoT Computing

https://penn-waves-lab.github.io/cis3990-24spring

Lecture 11: Batteryless Connectivity

Instructor: Mingmin Zhao (mingminz@cis.upenn.edu)

TA: Haowen Lai (hwlai@cis.upenn.edu)

Some material adapted from Omid Abari (UCLA)

Objectives of This Module

Learn the fundamentals, applications, and implications of Network technologies for Mobile and IoT Systems

- 1. What are the various classes of network technologies?
- 2. How do we choose the right technology for a given application?
- 3. What are the different routing architectures?
- 4. How does energy impact the system design?
- 5. How does batteryless connection work?

Focus of this lecture

Last Lecture











Bluetooth Classic and Bluetooth Low Energy (BLE)


How does BLE work?

Two parts:

- 1. Advertisements (aka beaconing) for device discovery
- 2. Connection phase for data exchange



BLE Advertisements are periodic




- Typical period: 100 ms
- Less frequent is fine
- Triggered advertisement are often a good idea

Trade-off between energy consumption and discovery latency

Extending communication range

What are the metrics that we care about?




Wireless Network Architectures

There are 3 kinds of wireless network architectures


Access Network

Device-to-device

Ad Hoc Network







e.g., WiFi, cellular

e.g., Bluetooth

e.g., leverage P2P to reach internet (crises)

One-hop

Multi-hop

Approach #4: Wireless routing metric: ETX

Minimize total transmissions per packet (ETX, 'Expected Transmission Count')

Link throughput $\approx 1/\text{Link ETX}$

<u>Delivery Ratio</u>		<u>Link ETX</u>	<u>Throughput</u>
100%		1	100%
50%		2	50%
33%	*	3	33%

Route ETX

Route ETX = Sum of link ETXs

Route ETX	<u>Throughput</u>
1	100%
2	50%
2	50%
3	33%
5	20%

Today's Topic: RFID and Batteryless Connection



























Forbes

Mar 8, 2021, 07:10am EST | 374 views

How RFID Helps Retail Companies Save Money

Walter Loeb Walter Loeb Senior Contributor ①

Retail

I cover major developments in the retail industry.

Feb 26, 2019, 08:44pm EST | 7,451 views

RFID

Japan Aims To Automate All Convenience Stores By 2025 With A New RFID Technology




Akiko Katayama Contributor ©
Food & Drink

1 This article is more than 2 years old.



RFID (Radio Frequency IDentification)

Access Control







Inventory control



Security Sensitive Applications







Tracking & Localization






Long-Range Payment Systems







RFID (Radio Frequency IDentification)









> 100 Billion in the world


VIDEOS WINDOWS 10 5G BEST VPNS CLOUD SECURITY AI MORE NEWSLETTERS ALL WINDOWS 10 TO SECURITY AI MORE NEWSLETTERS ALL WINDOWS 10 TO MUST READ: Everything you need to know about the Microsoft Exchange Server hack

PART OF A ZDNET SPECIAL FEATURE: CORONAVIRUS: BUSINESS AND TECHNOLOGY IN A PANDEMIC

Humble hero: How RFID is helping end the pandemic

A common technology takes on an uncommon mission: Distributing vaccines around the globe.

RFID: cheap battery-free stickers



History of RFIDs

- WWII: Aircraft IFF Transponder
 - + Identify Friend or Foe, Transmitter-Responder
- 1945: "The Thing" or "The Great Seal Bug"
 - "Gift" given by the Soviets to American ambassador
- 1980s: development of E-Toll transponders
- 2004: Auto-ID lab at MIT led to the birth of modern battery-free RFIDs
 - Goal: supply chain chain optimization
 - Paper: "Towards the 5 cent tag"





How are RFIDs different from standard wireless devices (e.g., WiFi, cellular)?

RFID Requirements

- Small form factor
- Massive scale
- Lifetime



RFID Constraints

- No battery
- Ultra-low cost
- Simple circuitr

Types of RFIDs

UHF (~900MHz)

HF (13.56MHz)

> LF (120-150kHz)

long range (few m)

short range (few cm)

Range of Operation

"need to tap"


Where do these fall?







Types of RFIDs



How does an RFID power up?

Harvests Energy from Reader's Signal

Inductive Coupling

LF (120- HF 150kHz) (13.56MHz)

Magnetic (Near Field)

Coil


Radiative

UHF (~900MHz)

Electromagnetic (Far Field)

Antenna


Inductive Coupling



UHF Backscatter Communication

- A flashlight emits a beam of light
- The light is reflected by the mirror

 The intensity of the reflected beam can be associated with a logical "0" or "1"




Backscatter Communication






Backscatter Communication




Uplink Communication




Simplified RFID schematic

Uplink Communication




EPC Gen2 Standard – MAC



Slotted Aloha:

- Reader allocates Q time slots and transmits a query at the beginning of each time slot
- Each tag picks a random slot and transmits a 16-bit random number
- In each slot:
 - RN16 decoded → Reader ACKs → Tags transmits 96-bit ID
 - Collision → Reader moves on to next slot
 - No reply → Reader moves on to next slot

EPC Gen2 – MAC




Let's consider an example with Q=4, no tag; and Q=4, 1 tag

Inefficient:

- If reader allocates large number of slots → Too many empty slots
- If reader allocates small number of slots → Too many collisions

EPC Gen2 - MAC



Inefficient:

- If reader allocates large number of slots → Too many empty slots
- If reader allocates small number of slots → Too many collisions
- If reader knows number of tags = N → Allocate K=N slots → 37% efficiency
- Downlink overhead

Significant work on "spanning trees", efficient scanning, decoding with collisions, etc.

Challenge: RFID Hacking for Fun and Profit

Ju Wang, Omid Abari and Srinivasan Keshav


{ju.wang,omid.abari,keshav}@uwaterloo.ca







What's the basic approach?








What's the basic approach?



 How do they isolate the impact of the environment vs the photoresists on RSS?

Solution: Differential Sensing to deal with environmental variations



- **Reference tag**: RSS1 ∝ Environment
- **Modified tag**: RSS2 ∝ Light + Environment

An E-Toll Transponder Network for Smart Cities

Smart City Services

Traffic Management

Detect Red-Light Runner Smart Parking








Key Problem: each service needs a new infrastructure

Smart Parking



Traffic Management




Ideally...

1) ONE Infrastructure


2) Ease of Maintenance

3) We don't want to add new devices to cars

Electronic Toll Transponders



Opportunities



One infrastructure for many smart services

Challenge: Interference

Wireless query

1

One car responds



Wireless query




All cars respond




How can we decode transponders despite Interference?

How can we decode transponders despite Interference?

One Transponder Responds → Decodable




Multiple Transponders Respond




Count cars: How to count despite interference?

Structure of the Signal




Variability due to manufacturing process

Structure of the Signal



Can count despite interference

Application of Batteryless RFID Localization to Robotic Picking





Summary of Lecture

- RFID background, history, and applications
- Types of RFIDs (LF, HF, UHF. Passive, Active)
- Principles of operation: energy harvesting & backscatter communication
- Etoll transponders for smart cities
- Dealing with interference
- RFID Localization

Objectives of This Module

Learn the fundamentals, applications, and implications of Network technologies for Mobile and IoT Systems



- l. What are the various classes of network technologies?
- 2. How do we choose the right technology for a given application?
- - 3. What are the different routing architectures?
- 4. How does energy impact the system design?
- - 5. How does batteryless connection work?

Module 3 review due: Mar 25th 11:59PM