

CIS 3990

Mobile and IoT Computing


<https://penn-waves-lab.github.io/cis3990-24spring>

Lecture 4: Device-Free Localization

Instructor: Mingmin Zhao (mingminz@cis.upenn.edu)


TA: Haowen Lai (hwlai@cis.upenn.edu)

Recap: Angle-of-Arrival




Recap: Angle-of-Arrival

$\theta = 90^\circ$



Recap: Angle-of-Arrival

$$\theta = 75^\circ$$




- **Combine constructively with the right delays**
- **Combine destructively without or with the incorrect delays**

$\theta = 75^\circ$

Multipath profile
(delay-and-sum):

$$P(\theta) = \left\| \sum_{k=1}^N h_i \exp(-j2\pi \frac{ks \cos(\theta)}{\lambda}) \right\|^2$$

Delay & Sum



Wireless Localization / Positioning

Past Lectures:

Device-based Localization




This Lecture:

Device-free Localization



Device-Free Localization (WiTrack, 2014)



Device in another room

Applications



Smart Homes




Energy Saving



Gaming & Virtual Reality


Measuring Distances



Round-Trip Distance = Reflection time x Speed of light


Measuring Reflection Time

Option 1: Transmit short pulse and listen for echo



Measuring Reflection Time

Option 1: Transmit short pulse and listen for echo




Capturing the pulse needs sub-nanosecond sampling!

Distance = Reflection time x Speed of light

"smallest distance resolution" = "smallest time" x Speed of light


10 cm → 0.3 ns

FMCW: Measure time by measuring frequency




**How does it look in time domain?
(and in comparison to single frequency)**


Wireless Signal at frequency f_0




Frequency vs. Time




FMCW signal



Frequency vs. Time




FMCW: Measure time by measuring frequency




How do we measure ΔF ?

Measuring ΔF





- Subtracting frequencies is easy (e.g., removing carrier in WiFi)
- Done using a mixer (low-power; cheap)



Let's talk about FFT




Basics of Fourier Transform



Measuring ΔF

- Subtracting frequencies is easy (e.g., removing carrier in WiFi)
- Done using a mixer (low-power; cheap)



$\Delta F \rightarrow$ Reflection Time $\rightarrow$ Distance (Round-trip)

FMCW

Frequency is linear in time;
hence phase is quadratic

FMCW Transmitted Signal:

$$x(t) = e^{j2\pi(\frac{k}{2}(t^2 + f_0 t))}$$

slope

FMCW Received Signal:

$$y(t) = \sum_i A_i e^{j2\pi(\frac{k}{2}((t-\tau_i)^2 + f_0(t-\tau_i)))}$$

Reflections linearly combine
over the wireless medium

reflector i


delay τ_i

FMCW after down-conversion:

$$y_b(t) = \sum_i A_i e^{j2\pi(k\tau_i t + f_0 \tau_i)}$$

frequency $k \tau_i$

Dealing with Multi-path




Direct furniture reflection:

eliminated by subtracting consecutive measurements


Needs User to Move!

Dynamic Multi-path



From Location to Tracking

- Send FMCW chirps respectively
- Estimate distance or location for chirp i
- Keep track of location over chirp index i (slow time)



Objectives of This Module

**Learn the fundamentals, applications, and implications of
localization, motion tracking, and sensing**

- ✓ 1. What are some motivating applications of localization and location-based services?
- ✓ 2. What are the unifying principles of positioning?
- ✓ 3. How do wireless positioning like GPS, Wi-Fi positioning, and Bluetooth ranging work?
- ✓ 4. What is wireless sensing?
- 5. How do visual positioning and tracking systems work?

iOS Lab 0 is out

- **Topic:** Get familiar with Xcode IDE and develop an OpenWeather API
- **Due:** Mon Feb 5th, 11:59 pm
- You will need MacBook + iPhone/iPad.
- We can help if you don't have one. Please coordinate with our TA.

Next Lecture

- **Time:** Mon Feb 5th
- **Topic:** Visual localization and tracking